




NBR Rubber Sheet



Nitrile Rubber is a copolymer of butadiene and acrylonitrile. NBR Rubber has good oil resistant performance, along with excellent abrasion and Tear Resistance, and permeability to gases.

SPECIFICATION

NBR RUBBER SHEET-COMMERCIAL GRADE(5%/10%/20% Nitrile Rubber Content)						
Item No.	Specific Gravity	Hardness (±5)	Tensile Strength	Elongation at break	Working Temp.	Compression set
	g/cm ³	Shore A	MPA	%	°C	%
HK1005	1.6	65+/-5	3	200	-30 ~ +120	50
HK1006	1.5	65+/-5	4	200	-30 ~ +150	40
HK1007	1.5	65+/-5	4	200	-30 ~ +150	40
NBR RUBBER SHEET-PURE GRADE(OIL RESISTANCE)						
Item No.	Specific Gravity	Hardness (±5)	Tensile Strength	Elongation at break	Working Temp.	Compression set
	g/cm ³	Shore A	MPA	%	°C	%
HK1008	1.5	65+/-5	5	200	-30 ~ +150	40
Thickness	1~50mm					
Width	1~1.5m					
Length	10~15m					
Color	Black, White, Red, Green, Brown.					
Note	One side or both side smooth or fabric surface can be supplied					
TEST:GB/T528-1998 GB/T3512-1989 GB/T531-1992(Air oven ageing 70°C, 72Hours)						
Tensile Strength	≤23%					
Elongation at Break	≤32%					

RESISTANCE				
Ozone	Oils	Concentrated acids and based	Dilute acids and based	Solvents
No	Yes for HK1008	No	Normal	Yes for HK1008